

# EXIDE®

## Batteries



**24 Months Warranty\***

\*for PRIVATE passenger vehicle use, subject to terms and conditions

### DIMENSIONAL SPECIFICATIONS

| OVERALL DIMENSIONS                       | METRIC (mm) |
|------------------------------------------|-------------|
| LENGTH                                   | 237         |
| WIDTH                                    | 171         |
| HEIGHT (bottom to top cover)             | 182         |
| TOTAL HEIGHT (bottom to top of terminal) | 208         |
| NOMINAL WEIGHT                           | 15.92 kg    |

### TECHNICAL SPECIFICATIONS

|                          |                                                                          |
|--------------------------|--------------------------------------------------------------------------|
| COLD CRANKING AMPS (CCA) | 525 CCA                                                                  |
|                          | Test reference: AS60095.1: 2022<br>Rated CCA DCH at 18°C for 30 sec      |
| CAPACITY (RC)            | 100 mins                                                                 |
|                          | Test reference: AS60095.1: 2022<br>25 Amps DCH at 10.5 V cut-off voltage |

|                |                                      |                                   |
|----------------|--------------------------------------|-----------------------------------|
| PART NUMBER    | MSDP22                               |                                   |
| CHARACTERISTIC | Lead-Acid (Enhanced Flooded Battery) |                                   |
| GROUP SIZE     | A46                                  |                                   |
| CASE AND LID   | Material                             | Polypropylene (PP)                |
|                | Handle                               | 1-pc PP handle                    |
|                | Case Colour                          | Black Casing                      |
|                | Lid Colour                           | Black Lid                         |
|                | Ledge / Hold-down                    | End Ledge & Front Ledge (EL & FL) |
|                | Vent                                 | Centralized venting               |

| TERMINAL DATA        | POSITIVE             | NEGATIVE             |
|----------------------|----------------------|----------------------|
| TYPE                 | Dual Fit Align (DFA) | Dual Fit Align (DFA) |
| TERMINAL HEIGHT (mm) | 24.0±0.20            | 24.0±0.20            |
| BOTTOM DIAMETER (mm) | 20.1±0.20            | 18.5±0.20            |
| TAPER                | 1:9                  | 1:9                  |
| POLARITY             |                      |                      |

|                                |                                               |
|--------------------------------|-----------------------------------------------|
| AMPERE-HOUR (20-HOUR CAPACITY) | 60 AH                                         |
|                                | Test reference: AS60095.1: 2022               |
|                                | Rated AH DCH at 10.5 V cut-off                |
| PLATE DESIGN                   | Lead-Calcium Alloy<br>Full Frame Plate Design |
| ELECTROLYTE                    | 36% H2SO4 at 15°C                             |

