

# EXIDE®

## Batteries



18 Months Warranty

|                |                                   |                     |
|----------------|-----------------------------------|---------------------|
| PART NUMBER    | N120JMFE                          |                     |
| CHARACTERISTIC | Lead-Acid Sealed Maintenance Free |                     |
| GROUP SIZE     | N120                              |                     |
| CASE AND LID   | Material                          | Polypropylene (PP)  |
|                | Handle                            | 2-pc rope handle    |
|                | Case Colour                       | Black Casing        |
|                | Lid Colour                        | Black Lid           |
|                | Ledge / Hold-down                 | No Ledge (NL)       |
|                | Vent                              | Centralized venting |

### DIMENSIONAL SPECIFICATIONS

| OVERALL DIMENSIONS                       | METRIC (mm) |
|------------------------------------------|-------------|
| LENGTH                                   | 505         |
| WIDTH                                    | 180         |
| HEIGHT (bottom to top cover)             | 210         |
| TOTAL HEIGHT (bottom to top of terminal) | 233         |
| NOMINAL WEIGHT                           | 36.43 kg    |

| TERMINAL DATA        | POSITIVE  | NEGATIVE  |
|----------------------|-----------|-----------|
| TYPE                 | SAE       | SAE       |
| TERMINAL HEIGHT (mm) | 18.5±1.50 | 18.5±1.50 |
| BOTTOM DIAMETER (mm) | 19.5±0.3  | 17.5±0.3  |
| TAPER                | 1:9       | 1:9       |
| POLARITY             |           |           |

### TECHNICAL SPECIFICATIONS

|                          |                                                                          |
|--------------------------|--------------------------------------------------------------------------|
| COLD CRANKING AMPS (CCA) | 900 CCA                                                                  |
|                          | Test reference: AS60095.1: 2022<br>Rated CCA DCH at 18°C for 30 sec      |
| CAPACITY (RC)            | 300 mins                                                                 |
|                          | Test reference: AS60095.1: 2022<br>25 Amps DCH at 10.5 V cut-off voltage |

|                                |                                               |
|--------------------------------|-----------------------------------------------|
| AMPERE-HOUR (20-HOUR CAPACITY) | 150 AH                                        |
|                                | Test reference: AS60095.1: 2022               |
|                                | Rated AH DCH at 10.5 V cut-off                |
| PLATE DESIGN                   | Lead-Calcium Alloy<br>Full Frame Plate Design |
| ELECTROLYTE                    | 36% H2SO4 at 15°C                             |

