



PART NUMBER	SSEFB-D23R		
CHARACTERISTIC	Lead-Acid (Enhanced Flooded Battery)		
GROUP SIZE	D23		
	Material	Polypropylene (PP)	
	Handle	1-pc PP handle	
	Case Colour	Black Casing	
CASE AND LID	Lid Colour	Black Lid	
	Ledge / Hold-down	Front Ledge (FL)	
	Vent	Centralized venting	

36 Months Warranty*

*for PRIVATE passenger vehicle use, subject to terms and conditions

D	$NJ \subseteq N$	NAL	CD	ECI	87	$\sim \Lambda T I$	ON	C
		NAL	OF					0

DIMENSIONAL OF EOIL TOAT				
OVERALL DIMENSIONS	METRIC (mm)	TERMINAL DATA	POSITIVE	NEGATIVE
LENGTH	232	TYPE	SAE	SAE
WIDTH	173	TERMINAL HEIGHT (mm)	18.5±1.50	18.5±1.50
HEIGHT (bottom to top cover)	200	BOTTOM DIAMETER (mm)	19.5±0.3	17.5±0.3
TOTAL HEIGHT (bottom to top of terminal)	225	TAPER	1:9	1:9
NOMINAL WEIGHT	18 kg	POLARITY	000	000

TECHNICAL SPECIFICATIONS

	650 CCA		
COLD CRANKING AMPS (CCA)	Test reference: AS60095.1: 2022 Rated CCA DCH at 18°C for 30 sec		
	110 mins		
CAPACITY (RC)	Test reference: AS60095.1: 2022 25 Amps DCH		
	at 10.5 V cut-off voltage		

	65 AH	
AMPERE-HOUR (20-HOUR CAPACITY)	Test reference: AS60095.1: 2022	
	Rated AH DCH at 10.5 V cut-off	
PLATE DESIGN	Lead-Calcium Alloy Full Frame Plate Design	
ELECTROLYTE	36% H2SO4 at 15°C	