



**36 Months Warranty\***

\*for PRIVATE passenger vehicle use, subject to terms and conditions

|                       |   |                     |
|-----------------------|---|---------------------|
| <b>PART NUMBER</b>    | <b>XD23R-AGM</b>                                |                     |
| <b>CHARACTERISTIC</b> | Valve Regulated Lead Acid (Absorbent Glass Mat) |                     |
| <b>GROUP SIZE</b>     | D23   |                     |
| <b>CASE AND LID</b>   | Material  | Polypropylene (PP)  |
|                       | Handle  | 1-pc PP handle      |
|                       | Case Colour                                     | Black Casing        |
|                       | Lid Colour                                      | Black Lid           |
|                       | Ledge / Hold-down                               | No Ledge (NL)       |
|                       | Vent  | Centralized venting |

#### DIMENSIONAL SPECIFICATIONS

| OVERALL DIMENSIONS                       | METRIC (mm) |
|--|-------------|
| LENGTH                                   | 220         |
| WIDTH                                    | 170         |
| HEIGHT (bottom to top cover)             | 200         |
| TOTAL HEIGHT (bottom to top of terminal) | 220         |
|  |             |
| NOMINAL WEIGHT                           | 15.1 kg     |

| TERMINAL DATA        | POSITIVE                   | NEGATIVE  |
|----------------------|----------------------------|-----------|
| TYPE                 | SAE                        | SAE       |
| TERMINAL HEIGHT (mm) | 18.5±1.50                  | 18.5±1.50 |
| BOTTOM DIAMETER (mm) | 19.5±0.3                   | 17.5±0.3  |
| TAPER                | 1:9                        | 1:9       |
|                      |                            |           |
| POLARITY             | ○ ○ ○ ○ ○ ○<br>- - - - - + |           |

#### TECHNICAL SPECIFICATIONS

|                          |   |
|--------------------------|---|
| COLD CRANKING AMPS (CCA) | 550 CCA   |
|                          | Test reference: AS60095.1: 2022<br>Rated CCA DCH at 18°C for 30 sec |
| CAPACITY (RC)            | -   |
|                          | Test reference: N/A   |

|                                |   |
|--------------------------------|---|
| AMPERE-HOUR (20-HOUR CAPACITY) | 50 AH   |
|                                | Test reference: AS60095.1: 2022               |
| PLATE DESIGN                   | Rated AH DCH at 10.5 V cut-off                |
| ELECTROLYTE                    | Lead-Calcium Alloy<br>Full Frame Plate Design |

