

Batteries



26	Months	2 M/2	PRO MELIX	l
-010	MATORIAL	5 VVa	Halliv	
			11 01110	

*for PRIVATE passenger vehicle use, subject to terms and conditions

PART NUMBER	U1LMF	
CHARACTERISTIC	Lead-Acid Sealed Maintenance Free	
GROUP SIZE	GU1	
	Material	Polypropylene (PP)
	Handle	1-pc PP handle
	Case Colour	Black Casing
CASE AND LID	Lid Colour	Black Lid
	Ledge / Hold-down	None
	Vent	Centralized venting

DIMENSIONAL SPECIFICATIONS

OVERALL DIMENSIONS	METRIC (mm)
LENGTH	196
WIDTH	128
HEIGHT (bottom to top cover)	159
TOTAL HEIGHT (bottom to top of terminal)	184
NOMINAL WEIGHT	8.95kg

TERMINAL DATA	POSITIVE	NEGATIVE
TYPE	U1	U1
TERMINAL HEIGHT (mm)	23.5±1.50	23.5±1.50
POLARITY	000	+

TECHNICAL SPECIFICATIONS

	350 CCA
COLD CRANKING AMPS (CCA)	Test reference: AS60095.1: 2022 Rated CCA DCH at 18°C for 30 sec
	45 mins
CAPACITY (RC)	Test reference: AS60095.1: 2022 25 Amps DCH at 10.5 V cut-off voltage


	35 AH	
AMPERE-HOUR (20-HOUR CAPACITY)	Test reference: AS60095.1: 2022	
	Rated AH DCH at 10.5 V cut-off	
PLATE DESIGN	Lead-Calcium Alloy Full Frame Plate Design	
ELECTROLYTE	36% H2SO4 at 15°C	

TOP VIEW

NYDROMETER EYE

FRONT VIEW

SIDE VIEW



Revision No. 00 Release Date: May 2025